



PRODUCT SPECIFICATION

Revision:1
Date:2012-4-27
Page: 1/1

Battery for Crane Remote Control AF-FUB05MB20



Models

HBC® FUB5AA

Compatibility

Battery Model: BA205030

Physical Characteristics

Dimension: 81.8 X 56.1 X 19.3 mm (3.22 X 2.21 X 0.76 inch)

Weight: 180 g (6.35 oz.)

Plastic Material: ABS

Electrical Characteristics

Chemistry: Ni-MH

Voltage: 6.0V

Capacity: Typical: 2050mAh; Minimum: 1950mAh

Cell: Gold Peak ReCyko GP210AAHCB

Operation Specification

Charging Voltage: 7.0 ~ 9.5 V

Charging Current: 0.2 ~ 2.0C

Discharging Current: 0.2 ~ 2.0C

Discharging End Voltage: 5.0 V

User Environment

Charging Temperature: ± 0 ~ +40°C (+32 ~ +104°F)

Discharging Temperature: -20 ~ +50°C (-4 ~ +122°F)

Storage Temperature: -20 ~ +50°C (-4 ~ +122°F)

Prolonged Storage Temp.: -20 ~ +30°C (-4 ~ +86°F)

Brand names are registered trademark of their respective owners

Addvantech Limited
www.addvantech.com
sales@addvantech.com