



PRODUCT SPECIFICATION

Revision:1
Date:2013-2-20
Page: 1/1

Battery for Crane Remote Control AF-HI6692MB



Models

HIAB® XS Drive

Compatibility

Battery Model: 378 6692

Physical Characteristics

Dimension: 120.6 X 50.0 X 21.7 mm (4.75 X 1.97 X 0.85 inch)

Weight: 190 g (6.70 oz.)

Plastic Material: ABS

Electrical Characteristics

Chemistry: Ni-MH

Voltage: 7.2V

Capacity: Typical: 1500mAh; Minimum: 1350mAh

Cell: Propine AA1500

Operation Specification

Charging Voltage: 8.4 ~ 11.4 V

Charging Current: 0.2 ~ 2.0C

Discharging Current: 0.2 ~ 2.0C

Discharging End Voltage: 6.0 V

User Environment

Charging Temperature: ± 0 ~ +40°C (+32 ~ +104°F)

Discharging Temperature: -20 ~ +50°C (-4 ~ +122°F)

Storage Temperature: -20 ~ +50°C (-4 ~ +122°F)

Prolonged Storage Temp.: -20 ~ +35°C (-4 ~ +95°F)

Brand names are registered trademark of their respective owners

Addvantech Limited
www.addvantech.com
sales@addvantech.com