



PRODUCT SPECIFICATION

Revision:1
Date:2010-2-10
Page: 1/1

Battery for Portable Data Collection Device

AS-LXEMX3L



Models

LXE® MX3, MX3Plus, MX3X



Compatibility

Battery Model: MX3A378BATT

Physical Characteristics

Dimension: 204.6 X 33.6 X 23.6 mm (8.06 X 1.32 X 0.93 inch)

Weight: 195 g (6.88 oz.)

Plastic Material: ABC

Electrical Characteristics

Chemistry: Li-ion

Voltage: 11.1V

Capacity: Typical: 2600mAh; Minimum: 2500mAh

Cell: Sanyo UR18650FM

Operation Specification

Charging Voltage: 12.6 ~ 13.5 V

Charging Current: 0.5 ~ 1.0C

Discharging Current: 0.5 ~ 1.0C

Discharging End Voltage: 9.0 V

User Environment

Charging Temperature: $\pm 0 \sim +40^{\circ}\text{C}$ ($+32 \sim +104^{\circ}\text{F}$)

Discharging Temperature: $-20 \sim +60^{\circ}\text{C}$ ($-4 \sim +140^{\circ}\text{F}$)

Storage Temperature: $-20 \sim +50^{\circ}\text{C}$ ($-4 \sim +122^{\circ}\text{F}$)

Prolonged Storage Temp.: $-20 \sim +30^{\circ}\text{C}$ ($-4 \sim +86^{\circ}\text{F}$)

LXE is a registered trademark of LXE Inc.

Addvantech Limited

www.addvantech.com

sales@addvantech.com